

VCM110-110-AL

C-mount Bi-telecentric Lens

- Optimized for 1/2.5"~1.1" C-Mount cameras;
- Largest FOV from 26mm upto 300mm;
- Excellent resolution for high pixel cameras;
- Low distortion, good telecentricity, big aperture and big depth of field for high end application.



Optical Specifications	
Magnification (x)	0.149
Object Field of View (Φmm)	111
Working Distance (mm)	251±3
Max Sensor Size (Φmm)	16.6(1")
Best Aperture (F/#)	6
Telecentricity typical (max) (deg)	<0.1
Distortion typical (max) (%)	<0.1
MTF30 (lp/mm)	>166
Depth of Field (mm)	±7
Length of I/O (mm)	542.5

Field of View (mm × mm)	
12.85×9.64 with KAI-04050	86.2×64.6
11.26×11.26 with CMV4000	75.5×75.5
12.50×10.00 with ICX674/694/814	83.8×67.1
Mechanical Specifications	
Mount	C
Length (mm)	274
Weight (kg)	4.17
Compatible Lighting	
Telecentric LED Lighting	VCL-110-xW-y Beam Diameter 110mm

Notes:

1. Depth of Field is calculated value, this value could be used for imaging test, but to get sharp image in application, half of calculated value is suggested.
2. Length of I/O = WD + Length + Back Focal Length.

